

MODEL NUMBER DESCRIPTION

LSP 1 2 1 1 - 2 -



ENCLOSURE SERIES

- 1 - White Powder Coat Door
- 2 - Brushed Stainless Steel
- 4 - Gray Powder Coat W/ Stainless Door & Trim

ENCLOSURE MOUNTING

- 1 - Surface Mount
- 2 - Flush Mount

ENCLOSURE STYLE

- 1 - Fuel Gas Systems
- 2 - Domestic Water
- 3 - Compressed Air
- 4 - Other (Specify)
- 5 - 4 pole contactor
- 6 - 8 pole contactor
- 7 - 30 amp contacts
- 8 - 40 amp contacts
- 9 - 50 amp contacts

OPTIONAL FEATURES

- F - In-Line Strainer
- U - Added Union
- LS - RF Module
- L - Door Louver
- EP - Explosion Proof Coil
- AT - Air Tight Bulkhead Fittings
- ATV - Air Tight Vented Bulkhead (Natural Gas & LP Applications Only)
- T - Panel Mount Tee-Handle Valve Operator

SOLENOID VALVE SIZE

- 1 - 1/2" IPS
- 2 - 3/4" IPS
- 3 - 1" IPS
- X - Indicates Electrical Enclosure W/ Contacts

OUTPUT CIRCUIT

- 1 - Single Output Circuit (Standard)
- 2 - Dual Output Circuits *

All output circuits are 24-VAC

Field Configurable Notification Output Circuit is Standard on all systems

* Second Output Circuit is intended for operation of a remotely located 24-VAC device