

MODEL NUMBER DESCRIPTION

RA - 1 1 X - 3 - S - LA

SERIES

RA - Standard Remote Access
LRA - W/ LS Enhancement

ENCLOSURE SERIES

Wall Panels per System (1)

MOUNTING STYLE

1 - Surface Mount
2 - Flush Mount

INTEGRATED SYSTEMS

- 0 - No EMS & Alarm Systems Integration
- 1 - EMS Active ON Input W/O Alarm Input
- 2 - EMS Active ON Input W/ Alarm Input
- 3 - EMS Active OFF Input W/O Alarm Input
- 4 - EMS Active OFF Input W/ Alarm Input
- 5 -(FK) First Keying Time OFF W/O Alarm Input
- 6 -(FK) First Keying Time OFF W/ Alarm Input
- 7 - Alarm Input W/O EMS

X In space indicates field configuration of Integration

Max. Output per Circuit 1.5 amp
3 amp. MAX @ 24 VAC

**RA SERIES
SINGLE
REMOTE ACCESS
SYSTEM
UTILITY CONTROLLERS**
Version 9.1

OPTION

LA - Furnish LA Wall Panel in lieu of RA Panel
R - Reset Switch

ENCLOSURE DOOR LATCH

S - Screw Driver Latch
K - Keyed Lock
H - Hand Knob

OUTPUT CIRCUIT CONFIGURATION

- 2 - Two Output Circuit
(Specify Circuits)
- 3 - Standard 3 Circuit Output
ELECTRIC - GAS - WATER
- 4 - 3 Circuit Output
ELECTRIC - GAS - FAN
- 5 - 3 Circuit Output
ELECTRIC - WATER - FAN
- 6 - 3 Circuit Output
WATER - GAS - FAN
- 7 - 4 Circuit Output
ELECTRIC - GAS - WATER - AIR
- 8 - 4 Circuit Output
ELECTRIC - GAS - AIR - FAN
- 9 - 4 Circuit Output
ELECTRIC - GAS - WATER - FAN
- 20 - Custom Assembly (Specify)

All Panels are provided with "PANIC" unless noted